



**LIFEMASTER® No VOC\***  
**Interior Flat Paint**  
**9100-XXXXN**

*DESCRIPTION*

**GLIDDEN PROFESSIONAL™ LIFEMASTER® No VOC\*** Flat Paint is a premium water-based acrylic finish that provides both a highly durable and washable finish for interior surfaces. GLIDDEN PROFESSIONAL LIFEMASTER No VOC\* Flat Paint has a quick dry-time and low odor, allowing rooms to be put back into service faster. It is the ideal coating for commercial and institutional applications such as schools, hospitals, nursing homes, hotels and offices. GLIDDEN PROFESSIONAL LIFEMASTER No VOC\* Interior Flat Paint contains anti-microbial agents that inhibit mold and mildew growth in the paint film.

**\*Colorants added to this base paint may increase VOC level significantly depending on color choice.**

*CERTIFICATIONS*

| AS OF 7/1/2009, COMPLIES WITH |     |
|-------------------------------|-----|
| MPI#                          | 143 |
| LEED                          | Yes |
| CHPS                          | Yes |
| GREENGUARD                    | Yes |
| AIM                           | Yes |
| OTC/LADCO                     | Yes |
| CARB                          | Yes |
| SCAQMD                        | Yes |

*PERFORMANCE DATA*

| CHARACTERISTIC:                           | RESULTS:                      |
|---|-------------------------------|
| Airless Spray Touch-Up**                  | ★★★★★☆☆☆☆                     |
| Dry Hide**                                | ★★★★★☆☆☆☆                     |
| Burnish Resistance**                      | ★★★★★☆☆☆☆                     |
| Shim Scrub Resistance**                   | ★★★★★☆☆☆☆                     |
| Washability**                             | ★★★★★☆☆☆☆                     |
| Sag Resistance                            | 12-16 mils wet                |
| Air and Substrate Application Temperature | 50° F (10° C) - 90° F (32° C) |
| Service Temperature Limits                | 200° F (93° C)                |
| Storage Temperature                       | 40° (4° C) F - 95° F (35° C)  |

\*\*Performance ratings are based on product comparisons to other products in that sheen range, performed at 77° F (25° C) 50% RH. Rating scale is from 1-10, 10 being the highest rating.

*COMPOSITION*

- Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

*SPECIFICATION*

Color:  
 White & custom colors

Clean-up Solvent:  
 Soap and water

Finish: **Flat**  
 Sheen: 10 units maximum @ 85°  
 Gloss: 2 - 8 units @ 60°

Density:  
 11.06 lbs/gal (1.33 kg/L)

Solids:  
 Volume - 33% +/- 1%  
 Weight - 50% +/- 1%

VOC:  
 0.0 lbs/gal (0.0 g/L)\*

Theoretical Coverage @ 1 mil dry:  
 522 sq ft/gal (13 m<sup>2</sup>/L)

Practical Coverage:  
 Apply at 425-475 sq ft/gal (10-12 m<sup>2</sup>/L).  
 Actual coverage may vary depending on substrate and application method.

Recommended Film Thickness:  
 3.4 - 3.8 mils wet  
 1.1 - 1.3 mils dry

Airless Spray Application:  
 Pressure - 2000 psi  
 Tip - .015" - .019"

Dry Time 77°F (25°C) & 50% RH:  
 To touch – 30-60 minutes  
 To recoat – 4 hours

Flame Spread Rating:  
 Class A (0-25) on non-combustible surfaces

Flash Point:  
 None

Shelf Life:  
 1 year minimum - unopened



www.gliddenprofessional.com

9 FINISHES PAINTING (09900)



## SURFACE PREPARATION

### GENERAL SURFACE PREPARATION:

All surfaces must be sound, dry, clean and free of oil, grease, dirt, rust, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

### NEW SURFACES:

#### Drywall:

- Joint compound must dry for two days before priming
- For lowest odor system, prime with 9116 LIFEMASTER No VOC\* Interior Primer Sealer
- 3210 GRIPPER® Interior Exterior Primer Sealer may also be used
- Product may be used as self-priming on drywall, used as a primer under it self

#### Wood:

- Set nails, fill with latex spackle
- Sand smooth
- Dust clean
- For lowest odor system, prime with 9116 LIFEMASTER No VOC\* Interior Primer Sealer
- 3210 GRIPPER Interior Exterior Primer Sealer may also be used

#### Concrete, Plaster and Masonry:

- Cure at least 30 days before painting
- pH must be 10.0 or lower
- Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping
- Rinse thoroughly with water and allow to dry
- Must be internally dry
- Remove loose aggregate
- Prime concrete and plaster with 9116 LIFEMASTER No VOC\* Interior Primer Sealer
- Product may be used as self-priming on concrete and plaster, used as a primer under it self
- Fill concrete block with 3010 Concrete Coatings Block Filler

#### Steel:

- Performance over hand or power tool cleaned surfaces is dependent on the degree of cleaning
- Prime with Devflex 4020PF Direct-to-Metal Primer, DEVGUARD® 4360 Low VOC Universal Primer or DEVGUARD 4160 Multi-Purpose Tank & Structural Primer

#### Galvanized Metal and Aluminum:

- Clean off oils and other contaminants
- Prime with 3210 GRIPPER Interior Exterior Primer Sealer, Devflex 4020PF Direct-to-Metal Primer, DEVGUARD 4360 Low VOC Universal Primer or DEVGUARD 4160 Multi-Purpose Tank & Structural Primer

#### Vinyl Wallcovering:

- Do not use over vinyl Wallcovering

### PREVIOUSLY PAINTED SURFACES:

- Wash to remove contaminants
- Rinse thoroughly with water and allow to dry
- Dull glossy areas by light sanding
- Remove sanding dust
- Remove loose paint
- Prime bare areas with primer specified under **NEW SURFACES**

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

\*Colorants added to this base paint may increase VOC level significantly depending on color choice.

## DIRECTIONS FOR USE

### TINTING:

Tint the appropriate base with DRAMATONE™ colorants. Other approved universal tinting colorants may be used.

### SPREADING RATE:

Apply at 425-475 sq ft/gal (10-12 m<sup>2</sup>/L). Actual coverage may vary depending on surface texture, porosity and application method. For best hiding of bright or accent colors, prime with the appropriate grey base. Certain shades of yellow, orange, pink and red may require multiple coats.

### APPLICATION:

Mix thoroughly before use. May be applied by brush, roller or airless spray. No thinning required. For airless spray, use a .015"-.019" tip at 2000 psi, adjust pressure as needed. Do not apply when the surface or air temperature is below 50°F (10°C). Provide good ventilation and warmth for normal drying. If painting will be interrupted for more than 15 minutes, keep brushes and rollers wet by wrapping them with tinfoil or plastic wrap. This will prevent the paint from drying in the equipment and will make clean up much easier when the job is finished.

### DRYING TIME:

At 77°F (25°C) and 50% R.H., dries to touch in 30-60 minutes and to recoat in four hours. Low temperature, high humidity, thick films or poor ventilation will increase these times.

### CLEAN-UP:

Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

### WASHING INSTRUCTIONS:

After 30 days or when paint has fully cured, areas may be washed using a non-abrasive, mild detergent solution and cellulose sponge.

## PRECAUTIONS

**WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.** For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.**

DS4-1105

## SHIPPING

### FREIGHT CLASSIFICATION:

Paint, Freezable

### PACKAGING:

1 gallon (3.785 L)  
5 gallons (18.925 L)

### FLASH POINT:

None



Akzo Nobel Paints LLC, Strongsville, Ohio 44136



www.gliddenprofessional.com

**LIMITATION OF LIABILITY** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.